



Brake Motors - IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains

IE3

UL

SE

CCC

TECHNICAL DATA

Motor Type

AMPEBY 100L BA4 - 3 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBY 100L BA
Poles	4
kW	3
HP	4
rpm	1460
Mn Nm	19.5
η 50%	86.1
η 75%	87.8
η 100%	87.7
cos Phi	0.82
I_N	6.0
I_A/I_N	8.5
M_A/M_N	2.5
M_K/M_N	3.0

J 10⁻³ kgm²	7.24
Mb max Nm	40(75) ²)
zL ¹) c/h	4550
kg	34.3

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.