



Brake Motors - IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains

IE3

UL

SE

CCC

TECHNICAL DATA

Motor Type

AMPEBZ 90L BA2 - 2.2 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBZ 90L BA
Poles	2
kW	2.2
HP	3
rpm	2880
Mn Nm	7.3
η 50%	85.0
η 75%	86.2
η 100%	86.5
cos Phi	0.82
I_N	4.6
I_A/I_N	9.2
M_A/M_N	4.0
M_K/M_N	4.2

J 10⁻³ kgm²	2.13
Mb max Nm	15(40) ²)
zL ¹) c/h	2400
kg	25.6

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.