



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 63Z AA - 0.18 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 63Z AA
Poles	2
kW	0.18
HP	0.25
rpm	2790
Mn Nm	0.62
η 50%	54
η 75%	58
η 100%	63
cos Phi	0.73
I_N 400 V	0.6
I_N 380-400 V	0.65
I_A/I_N	3.7
M_A/M_N	3

M_K/M_N	3.1
J 10 ⁻³ kgm ²	0.19
Mb max Nm	3.5
zL ¹⁾ c/h	6300
kg	5.7

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.