



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 80Z AA - 0.75 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 80Z AA
Poles	2
kW	0.75
HP	1
rpm	2840
Mn Nm	2.52
η 50%	66.3
η 75%	71.5
η 100%	73
cos Phi	0.78
I _N 400 V	1.9
I _N 380-400 V	2
I _A /I _N	5
M _A /M _N	2.8

M_K/M_N	2.9
$J \cdot 10^{-3} \text{ kgm}^2$	0.7
$M_b \text{ max Nm}$	7.5(15) ²⁾
$zL^{-1}) \text{ c/h}$	3350
kg	12.6

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	60

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.