



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 90S AA4 - 1.1 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 90S AA
Poles	4
kW	1.1
HP	1.5
rpm	1400
Mn Nm	7.5
η 50%	75.8
η 75%	76
η 100%	75.4
cos Phi	0.78
I_N 400 V	2.7
I_N 380-400 V	2.9
I_A/I_N	5.2
M_A/M_N	2.5

M_K/M_N	2.8
J 10⁻³ kgm²	2.36
Mb max Nm	15(40) ²
zL 1) c/h	5000
kg	18

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.