



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMBY 132M BA4 - 7.5 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 132M BA
Poles	4
kW	7.5
HP	10
rpm	1460
Mn Nm	49.7
η 50%	85.8
η 75%	87.6
η 100%	86.0
cos Phi	0.84
I_N 400 V	14.9
I_N 380-400 V	15.5
I_A/I_N	8.2
M_A/M_N	2.6

M_K/M_N	3.7
J 10⁻³ kgm²	28.7
Mb max Nm	75(150) ²
zL 1) c/h	1800
kg	69

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	59

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.