


**Brake Motors - IE3/IE2/IE1**

**STANDARD EFFICIENCY MOTORS - IE1**



- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



**TECHNICAL DATA**

**Motor Type** AMBY 80Z AA6 - 0.37 kW - 6 poles - 400V - 50Hz

**PERFORMANCE DATA**

|                                    |             |
|------------------------------------|-------------|
| <b>Type</b>                        | AMBY 80Z AA |
| <b>Poles</b>                       | 6           |
| <b>kW</b>                          | 0.37        |
| <b>HP</b>                          | 0.5         |
| <b>rpm</b>                         | 920         |
| <b>Mn Nm</b>                       | 3.84        |
| $\eta$ 50%                         | 47          |
| $\eta$ 75%                         | 58          |
| $\eta$ 100%                        | 60          |
| <b>cos Phi</b>                     | 0.7         |
| <b>I<sub>N</sub> 400 V</b>         | 1.25        |
| <b>I<sub>N</sub> 380-400 V</b>     | 1.3         |
| <b>I<sub>A</sub>/I<sub>N</sub></b> | 2.7         |
| <b>M<sub>A</sub>/M<sub>N</sub></b> | 1.6         |

|  |                      |
|--|----------------------|
| <b><math>M_K/M_N</math></b>              | 2.1                  |
| <b>J 10<sup>-3</sup> kgm<sup>2</sup></b> | 1.94                 |
| <b>Mb max Nm</b>                         | 7.5(15) <sup>2</sup> |
| <b>zL 1) c/h</b>                         | 9000                 |
| <b>kg</b>                                | 12.2                 |

## Mechanical Data

|                                     |                               |
|-------------------------------------|-------------------------------|
| <b>Design</b>                       | ALUMINIUM                     |
| <b>Degree of protection</b>         | IP 55                         |
| <b>Bearings DE/NDE</b>              | 6204/2Z                       |
| <b>Lubrication grease</b>           | low & high temperature grease |
| <b>Regreasing device horizontal</b> | permanent lubrication         |
| <b>Regreasing device vertical</b>   | permanent lubrication         |
| <b>Cooling</b>                      | IC 411                        |
| <b>Vibration Level</b>              | A (normal)                    |
| <b>Noise Lpa db(A)</b>              | 40                            |

## Electrical Data

|                              |                |
|------------------------------|----------------|
| <b>Voltage</b>               | 400V - 50Hz    |
| <b>Connection</b>            | ?/Y 230/400V   |
| <b>Duty type</b>             | S1             |
| <b>Thermal protection</b>    | na             |
| <b>Insulation class</b>      | F              |
| <b>Direction of rotation</b> | bidirectional  |
| <b>Ambient temperature</b>   | -20°C / +40 °C |
| <b>Altitude</b>              | 1000 m.a.s.l.  |