



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMBZ 112M BA4 - 5.5 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 112M BA
Poles	4
kW	5.5
HP	7.5
rpm	1430
Mn Nm	36.7
η 50%	84.1
η 75%	84.8
η 100%	84
cos Phi	0.83
I_N 400 V	11.4
I_N 380-400 V	11.7
I_A/I_N	6.5
M_A/M_N	2.2

M_K/M_N	2.9
J 10⁻³ kgm²	14.42
Mb max Nm	75
zL 1) c/h	2500
kg	48.3

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6306/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	53

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.