



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBZ 90L BA6 - 1.1 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 90L BA
Poles	6
kW	1.1
HP	1.5
rpm	920
Mn Nm	11.4
η 50%	72
η 75%	73.5
η 100%	73
cos Phi	0.66
I_N 400 V	3.3
I_N 380-400 V	3.4
I_A/I_N	3
M_A/M_N	1.7

M_K/M_N	1.7
J 10 ⁻³ kgm ²	4.73
Mb max Nm	40
zL ¹⁾ c/h	7050
kg	23.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	46

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.