


Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1



- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMS 132M ZA6 - 5.5 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 132M ZA
Poles	6
kW	5.5
HP	7.5
rpm	950
Mn Nm	55
η 50%	82.2
η 75%	83.6
η 100%	83.6
cos Phi	0.71
I_N 400 V	13.5
I_N 380-400 V	13.5
I_A/I_N	4.1
M_A/M_N	2.2

M_K/M_N	2.2
J 10^{-3} kgm²	42
Mb max Nm	30
zL ¹⁾ c/h	1400
kg	65

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	57

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.