



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMS 160M ZA6 - 7.5 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 160M ZA
Poles	6
kW	7.5
HP	10
rpm	970
Mn Nm	74
η 50%	85.7
η 75%	87.5
η 100%	87.6
cos Phi	0.78
I_N 400 V	15.9
I_N 380-400 V	16.2
I_A/I_N	6.2
M_A/M_N	2.8

M_K/M_N	3.2
J 10⁻³ kgm²	108
Mb max Nm	30
zL 1) c/h	900
kg	102.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	58

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.