



Single-phase Motors - IE2

STANDARD MOTORS

- Customisation at all levels



TECHNICAL DATA

Motor Type

AMME 90L AA4 - 1.1 kW - 4 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMME 90L AA
Poles	4
kW	1.1
HP	1.5
rpm	1415
η 100%	70
cos Phi	0.93
I_N 230V	7.4
I_N 220-240V	7.8
I_A/I_N	4.8
M_A/M_N	2.0
M_K/M_N	1.5
J 10^{-3} kgm ²	3.13
kg	15.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	25
Starting Capacitor Microf	108 - 130
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.