

Pacchetti Motore Sincrono PM e Azionamento - IES2



MOTORE PM E AZIONAMENTO COMBINATO - IES2

- Soluzione Plug & Play
- Totale controllo della velocità
- Protezione IP20 o IP66 / NEMA 4X outdoor
- Tre configurazioni del pacchetto

HP Combi
Smart Flow Plus
solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPC 90 1800_Smart_IP66 3 kW - 1800 rpm | Drive three-phase - 200-240V

PERFORMANCE DATA

Package Type	HPC 90 1800_Smart_IP66
Rated Speed rpm	1800
Rated Power kW	3
Rated Power HP	4
Rated Torque Nm	15.9
Peak Torque Nm	47.7
Voltage Constant Vs	1.45
Torque Constant Nm/A	2.5
B.E.M.F. @ rated speed Vrs	272
Rated Current Arms	6.3
Motor Efficiency IE code	IE5
Motor Efficiency η %	91.0
Motor Weight Kg	17

Drive Type	Smart
Drive Size	2
Drive Efficiency IE code	IE2
HPC Efficiency IE code	IES2
HPC Efficiency ? %	90.6

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6206 2Z
Bearings NDE	6304 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Motor Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.

Drive Data

Drive Type	Smart
Drive Size	2
Supply Voltage	three-phase
Drive Voltage	200-240V
Safety Function	-
Drive Torque	constant/variable
Fieldbus	CANopen; Modbus RTU

Inputs	2 Digital; 2 Analog / Digital selectable
Outputs	1 Analog/Digital; 1 Relay
Degree of Protection	IP 66