

Pacchetti Motore Sincrono PM e Azionamento - IES2



MOTORE PM E AZIONAMENTO COMBINATO - IES2

- Soluzione Plug & Play
- Totale controllo della velocità
- Protezione IP20 o IP66 / NEMA 4X outdoor
- Tre configurazioni del pacchetto

HP Combi
Smart Flow Plus
solutions to meet your needs

IES2

TECHNICAL DATA

Motor Type

HPC 90 3600_Smart_IP66 5.5 kW - 3600 rpm | Drive three-phase - 200-240V

PERFORMANCE DATA

| | |
|---|------------------------|
| Package Type | HPC 90 3600_Smart_IP66 |
| Rated Speed rpm | 3600 |
| Rated Power kW | 5.5 |
| Rated Power HP | 7.5 |
| Rated Torque Nm | 14.6 |
| Peak Torque Nm | 43.8 |
| Voltage Constant Vs | 0.73 |
| Torque Constant Nm/A | 1.26 |
| B.E.M.F. @ rated speed Vrs | 272 |
| Rated Current Arms | 11.6 |
| Motor Efficiency IE code | IE5 |
| Motor Efficiency η % | 91.6 |
| Motor Weight Kg | 16 |

| | |
|---------------------------------|-------|
| Drive Type | Smart |
| Drive Size | 3 |
| Drive Efficiency IE code | IE2 |
| HPC Efficiency IE code | IES2 |
| HPC Efficiency ? % | 90.6 |

Mechanical Data

| | |
|-----------------------------|-------------------------------|
| Design | ALUMINIUM |
| Degree of protection | IP 55 |
| Bearings DE | 6206 2Z |
| Bearings NDE | 6304 2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |

Electrical Data

| | |
|------------------------------|----------------|
| Motor Supply Voltage | 400V - 50Hz |
| Duty type | S1 |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -15°C / +40 °C |
| Altitude | 1000 m.a.s.l. |

Drive Data

| | |
|------------------------|---------------------|
| Drive Type | Smart |
| Drive Size | 3 |
| Supply Voltage | three-phase |
| Drive Voltage | 200-240V |
| Safety Function | - |
| Drive Torque | constant/variable |
| Fieldbus | CANopen; Modbus RTU |

| | |
|-----------------------------|--|
| Inputs | 2 Digital; 2 Analog / Digital selectable |
| Outputs | 1 Analog/Digital; 1 Relay |
| Degree of Protection | IP 66 |