



Motori Sincroni PM - IE6/IE5

MOTORI ULTRA PREMIUM EFFICIENCY - IE5

- Rendimento IE5 Ultra Premium Efficiency
- L'affidabilità di un motore AC con le prestazioni di un Brushless
- Gamma completa e sempre disponibile a stock

IE5 

TECHNICAL DATA

Motor Type

IE5 HPS 56 3000 5 0.25 kW - 3000 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE5 HPS 56 3000 5
Rated Speed rpm	3000
Rated Power kW	0.25
Rated Power HP	0.33
Rated Torque Nm	0.8
Peak torque Nm	2.4
Voltage constant Vs	0.87
Torque constant Nm/A	1.5
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	0.5
Efficiency IE code	IE5
Efficiency η %	75.8
Weight Kg	2.8

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6202 2Z
Bearings NDE	6201 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.