



Motori Sincroni PM - IE6/IE5

MOTORI ULTRA PREMIUM EFFICIENCY - IE5

- Rendimento IE5 Ultra Premium Efficiency
- L'affidabilità di un motore AC con le prestazioni di un Brushless
- Gamma completa e sempre disponibile a stock

IE5 

TECHNICAL DATA

Motor Type

IE5 HPS 160 3000 634 30 kW - 3000 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE5 HPS 160 3000 634
Rated Speed rpm	3000
Rated Power kW	30
Rated Power HP	40
Rated Torque Nm	95.4
Peak torque Nm	239
Voltage constant Vs	0.87
Torque constant Nm/A	1.51
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	63.4
Efficiency IE code	IE5
Efficiency η %	94.9
Weight Kg	90

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6310 2Z
Bearings NDE	6310 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.