



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 90L CA2 - 2.2 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 90L CA
Poles	2
kW	2.2
HP	3
rpm	2860
Mn Nm	7.3
η 50%	81.5
η 75%	82.0
η 100%	81.8
cos Phi	0.81
I _N 400V	4.9
I _N 380-420V	4.9
I _A /I _N	7.1
M _A /M _N	4.1

M_S/M_N	3.6
M_K/M_N	4.0
$J \cdot 10^{-3} \text{ kgm}^2$	1.68
kg	16.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.