



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 160L RA2 - 22 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 160L RA
Poles	2
kW	22
HP	30
rpm	2940
Mn Nm	71.5
η 50%	88.7
η 75%	90.5
η 100%	90.4
cos Phi	0.90
I_N 400V	39.1
I_N 380-420V	39.4
I_A/I_N	8.4
M_A/M_N	3.0

M_S/M_N	2.6
M_K/M_N	3.7
$J \cdot 10^{-3} \text{ kgm}^2$	57.0
kg	108.7

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	74

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.