



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 56Z BA4 - 0.09 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 56Z BA
Poles	4
kW	0.09
HP	0.12
rpm	1330
Mn Nm	0.6
η 50%	43.0
η 75%	47.0
η 100%	51.0
cos Phi	0.74
I _N 400V	0.35
I _N 380-420V	0.40
I _A /I _N	2.5
M _A /M _N	2.2

M_S/M_N	2.1
M_K/M_N	2.2
$J \cdot 10^{-3} \text{ kgm}^2$	0.16
kg	2.9

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6201/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	38

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.