



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 71Z AA4 - 0.25 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 71Z AA
Poles	4
kW	0.25
HP	0.33
rpm	1340
Mn Nm	1.8
η 50%	55.0
η 75%	59.0
η 100%	64.0
cos Phi	0.66
I _N 400V	0.90
I _N 380-420V	1.00
I _A /I _N	3.2
M _A /M _N	1.9

M_S/M_N	1.8
M_K/M_N	2.0
$J \cdot 10^{-3} \text{ kgm}^2$	0.65
kg	5.7

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.