



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type AM 100L CA4 - 4.0 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 100L CA
Poles	4
kW	4.0
HP	5.5
rpm	1400
Mn Nm	27.3
η 50%	80.8
η 75%	81.8
η 100%	80.4
cos Phi	0.78
I_N 400V	9.2
I_N 380-420V	9.3
I_A/I_N	6.0
M_A/M_N	2.6

M_S/M_N	2.4
M_K/M_N	2.9
J 10⁻³ kgm²	6.3
kg	25.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V - ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.