



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type AM 132M TA6 - 7.5 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 132M TA
Poles	6
kW	7.5
HP	10
rpm	960
Mn Nm	74.6
η 50%	82.8
η 75%	83.5
η 100%	82.9
cos Phi	0.75
I_N 400V	17.4
I_N 380-420V	17.6
I_A/I_N	5.0
M_A/M_N	2.3

M_S/M_N	1.9
M_K/M_N	2.8
J 10⁻³ kgm²	46.7
kg	64.1

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	57

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.