



**Motori Asincroni Trifase - IE4/IE3/IE2/IE1**

**MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS**

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

**Motor Type** AMQE 160M BA2 - 11 kW - 2 poles - 400V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMQE 160M BA
<b>Poles</b>	2
<b>kW</b>	11
<b>HP</b>	15
<b>rpm</b>	2965
<b>Mn Nm</b>	35.6
$\eta$ 50%	89.5
$\eta$ 75%	91.7
$\eta$ 100%	92.6
<b>cos Phi</b>	0.84
<b>I<sub>N</sub> 400V</b>	20.3
<b>I<sub>N</sub> 460V</b>	-
<b>I<sub>N</sub> 575V</b>	-
<b>I<sub>A</sub>/I<sub>N</sub></b>	13.8

$M_A/M_N$	5.1
$M_S/M_N$	4.5
$M_K/M_N$	5.3
$J \cdot 10^{-3} \text{ kgm}^2$	53.4
kg	88.9

## Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	74

## Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.