



**Motori Asincroni Trifase - IE4/IE3/IE2/IE1**

**MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS**

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

**Motor Type** AMQE 315L G2 - 200 kW - 2 poles - 400V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMQE 315L G
<b>Poles</b>	2
<b>kW</b>	200
<b>HP</b>	270
<b>rpm</b>	2980
<b>Mn Nm</b>	640.9
$\eta$ 50%	94.6
$\eta$ 75%	96.5
$\eta$ 100%	96.5
<b>cos Phi</b>	0.91
<b>I<sub>N</sub> 400V</b>	329.0
<b>I<sub>N</sub> 460V</b>	-
<b>I<sub>N</sub> 575V</b>	-
<b>I<sub>A</sub>/I<sub>N</sub></b>	7.2

$M_A/M_N$	1.8
$M_S/M_N$	1.7
$M_K/M_N$	2.2
$J \cdot 10^{-3} \text{ kgm}^2$	2380
kg	1200

## Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6317 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	1.000 hours
Regreasing device vertical	1.000 hours
Grease Quantity	50 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

## Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.