



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 280S G6 - 45 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 280S G
Poles	6
kW	45
HP	60
rpm	990
Mn Nm	434.1
η 50%	92.9
η 75%	94.8
η 100%	94.8
cos Phi	0.85
I_N 400V	80.6
I_N 460V	-
I_N 575V	-
I_A/I_N	7.3

M_A/M_N	2.0
M_S/M_N	2.0
M_K/M_N	2.0
$J \cdot 10^{-3} \text{ kgm}^2$	1390
kg	530

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6317 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	6.000 hours
Regreasing device vertical	6.000 hours
Grease Quantity	35 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.