



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 315M G6 - 90 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 315M G
Poles	6
kW	90
HP	125
rpm	990
Mn Nm	868.2
η 50%	93.7
η 75%	95.6
η 100%	95.6
cos Phi	0.85
I_N 400V	160.0
I_N 460V	-
I_N 575V	-
I_A/I_N	6.7

M_A/M_N	2.0
M_S/M_N	2.0
M_K/M_N	2.0
$J \cdot 10^{-3} \text{ kgm}^2$	4780
kg	1070

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	NU319 - 6319 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	5.500 hours
Regreasing device vertical	5.500 hours
Grease Quantity	50 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.