



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 90S AA4 - 1.1 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 90S AA
Poles	4
kW	1.1
HP	1.5
rpm	1440
Mn Nm	7.3
η 50%	83.3
η 75%	84.3
η 100%	84.1
cos Phi	0.75
I_N	2.5
I_A/I_N	7.1
M_A/M_N	4.3
M_S/M_N	3.4

M_K/M_N	4.4
J 10⁻³ kgm²	3.6
kg	15.8

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.