



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 250M PG4 - 55 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 250M PG
Poles	4
kW	55
HP	75
rpm	1485
Mn Nm	353.7
η 50%	92.7
η 75%	94.6
η 100%	94.6
cos Phi	0.86
I_N	97.6
I_A/I_N	7.4
M_A/M_N	2.2
M_S/M_N	2.1

M_K/M_N	2.3
J 10⁻³ kgm²	660
kg	442

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6314 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	4.500 hours
Regreasing device vertical	4.500 hours
Grease Quantity	35 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	76

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.