




Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 100L AA6 - 1.1 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 100L AA
Poles	6
kW	1.1
HP	1.5
rpm	960
Mn Nm	10.9
η 50%	78.9
η 75%	81.3
η 100%	81.0
cos Phi	0.65
I_N	3.0
I_A/I_N	6.2
M_A/M_N	2.2
M_S/M_N	1.8

M_K/M_N	2.8
J 10⁻³ kgm²	11.6
kg	25

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	51

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.