



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI PREMIUM EFFICIENCY - IE3/CURUS

- Motori IE3 Premium Efficiency già dal 2010
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMPE 160L ZA6 - 9.2 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 160L ZA
Poles	6
kW	9.2
HP	12.4
rpm	970
Mn Nm	87.6
η 50%	88.9
η 75%	90.1
η 100%	89.8
cos Phi	0.74
I_N	19.9
I_A/I_N	8.3
M_A/M_N	3.1
M_S/M_N	2.2

M_K/M_N	3.5
J 10⁻³ kgm²	136.0
kg	105

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	58

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.