



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B10.42J 42 Nm - 2000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B10.42J
Stall torque (Deltat=105°C) Mo Nm	42
Rated speed n rpm	2000
Rated power P _n kW	7.6
Rated torque (Deltat=105°C) Mn Nm	36.1
Peak torque M _{pk} Nm	180
Max speed n _{max} rpm	4000
Moment of inertia J 10 ⁻³ Kgm ²	74
Peack torque acceleration a _{pk} rad/sec ²	24324
Thermal time constant T _{th} min	46
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.45
Inductance phase to phase L _w mH	8.8

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	17.2
Rated current I_n Arms	14.8
Peak current I_{pk} Arms	105
Power connector size	7/1
Weight kg	30

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6208 2ZC3WT
Bearings NDE	6206 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140