



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B13.C2I 162 Nm - 1500 rpm - 6 poles - 400V

PERFORMANCE DATA

Type	B13.C2I
Stall torque (Deltat=105°C) Mo Nm	162
Rated speed n rpm	1500
Rated power P _n kW	22.3
Rated torque (Deltat=105°C) Mn Nm	142
Peak torque M _{pk} Nm	345
Max speed n _{max} rpm	3600
Moment of inertia J 10 ⁻⁴ Kgm ²	192
Peack torque acceleration a _{pk} rad/sec ²	17969
Thermal time constant T _{th} min	90
Voltage constant k _e V _s	1.88
Torque constant k _t Nm/A	3.26
Resistance phase to phase (20°C) R _w ?	0.2
Inductance phase to phase L _w mH	6.1

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	49.7
Rated current I_n Arms	43.6
Peak current I_{pk} Arms	136
Power connector size	7/1.5
Weight kg	92

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6309 2ZC3WT
Bearings NDE	6208 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	6
Voltage	400V
Thermal protection threshold θ_{max} °C	140