



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type B71.17U 22.1 Nm - 4500 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B71.17U
Stall torque (Deltat=105°C) Mo Nm	22.1
Rated speed n rpm	4500
Rated power P_n kW	6.5
Rated torque (Deltat=105°C) Mn Nm	13.9
Peak torque M_{pk} Nm	47.3
Max speed n_{max} rpm	5000
Moment of inertia J 10?? Kgm²	9.80
Thermal time constant T_{th} min	16
Voltage constant k_e V_s	0.63
Torque constant k_t Nm/A	1.09
Resistance phase to phase (20°C) R_w ?	0.34
Inductance phase to phase L_w mH	4.3
B.E.M.F. @ rated speed E_n Vrms	296

Stall current I_o Arms	20.3
Rated current I_n Arms	12.7
Peak current I_{pk} Arms	59.1
Connection type/size	7/1
Weight kg	9.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205
Bearings NDE	6203
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140