



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type

B56.I5U 5.5 Nm - 6000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B56.I5U
Stall torque (Deltat=105°C) Mo Nm	5.5
Rated speed n rpm	6000
Rated power P _n kW	2.0
Rated torque (Deltat=105°C) Mn Nm	3.2
Peak torque M _{pk} Nm	18.7
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	1.8
Thermal time constant T _{th} min	22
Voltage constant k _e V _s	0.42
Torque constant k _t Nm/A	0.73
Resistance phase to phase (20°C) R _w ?	1.06
Inductance phase to phase L _w mH	5.70
B.E.M.F. @ rated speed E _n Vrms	264

Stall current I_o Arms	7.6
Rated current I_n Arms	4.4
Peak current I_{pk} Arms	34.7
Connection type/size	7/1
Weight kg	5.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6204
Bearings NDE	6003
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140