



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type AMHEBZ 71Z CA4 - 0.55 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBZ 71Z CA
Poles	4
kW	0.55
HP	0.75 ¹
rpm	1410
Mn Nm	3.8
η 50%	71.5
η 75%	75.5
η 100%	77.1
cos Phi	0.71
I_N	1.5
I_A/I_N	3.6
M_A/M_N	2.4
M_K/M_N	2.4

J 10⁻³ kgm²	1.11
Mb max Nm	7.5
zL 1) c/h	7800
kg	10.1

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.