



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMHEBZ 90L BA4 - 1.5 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBZ 90L BA
Poles	4
kW	1.5
HP	2
rpm	1430
Mn Nm	10
η 50%	82
η 75%	83.5
η 100%	83
cos Phi	0.77
I_N	3.4
I_A/I_N	6.4
M_A/M_N	3.9
M_K/M_N	4

J 10⁻³ kgm²	3.98
Mb max Nm	40
zL 1) c/h	4150
kg	24.8

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.