



Motori Autofrenanti - IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMHES 63Z BA2 - 0.25 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHES 63Z BA
Poles	2
kW	0.25
HP	0.33
rpm	2790
Mn Nm	0.9
η 50%	60.8
η 75%	67.2
η 100%	64.8
cos Phi	0.68
I_N	0.8
I_A/I_N	4.5
M_A/M_N	3.2
M_K/M_N	3.3

J 10⁻³ kgm²	0.45
Mb max Nm	3
zL ¹⁾ c/h	3150
kg	5.6

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.