

Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMBY 63Z BA4 - 0.18 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 63Z BA
Poles	4
kW	0.18
HP	0.25
rpm	1330
Mn Nm	1.29
η 50%	47
η 75%	50
η 100%	58
cos Phi	0.70
I_N 400 V	0.65
I_N 380-400 V	0.7
I_A/I_N	2.3
M_A/M_N	1.9

M_K/M_N	1.9
J 10 ⁻³ kgm ²	0.35
Mb max Nm	3.5
zL ¹⁾ c/h	12500
kg	6.2

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	38

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.