



Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type AMBZ 160L ZA6 - 11 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 160L ZA
Poles	6
kW	11
HP	15
rpm	960
Mn Nm	109
η 50%	88.1
η 75%	88.5
η 100%	87.8
cos Phi	0.78
I_N 400 V	23.4
I_N 380-400 V	24
I_A/I_N	6
M_A/M_N	2.5

M_K/M_N	3.5
J 10⁻³ kgm²	139
Mb max Nm	150(250) ²
zL 1) c/h	1120
kg	143

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	58

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.