

Motori Autofrenanti - IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Completamente customizzabile anche per ambienti off shore
- Alta progettualità e prestazioni elevate
- Qualità totale con il controllo completo su tutti i componenti



TECHNICAL DATA

Motor Type

AMS 80Z CA4 - 1.1 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 80Z CA
Poles	4
kW	1.1
HP	1.5
rpm	1385
Mn Nm	7.6
η 50%	73.4
η 75%	75.7
η 100%	75
cos Phi	0.77
I_N 400 V	2.8
I_N 380-400 V	2.9
I_A/I_N	4.4
M_A/M_N	2.5

M_K/M_N	2.6
J 10 ⁻³ kgm ²	3.16
Mb max Nm	7
zL ¹⁾ c/h	3750
kg	13.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.