



Motori Monofase - IE2

MOTORI STANDARD

- Personalizzazione a tutti i livelli



TECHNICAL DATA

Motor Type

AMME 63Z AA2 - 0.12 kW - 2 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMME 63Z AA
Poles	2
kW	0.12
HP	0.16
rpm	2810
η 100%	67.1
cos Phi	0.90
I_N 230V	0.90
I_N 220-240V	1
I_A/I_N	2.5
M_A/M_N	1.9
M_K/M_N	1.5
J 10 ⁻³ kgm ²	0.11
kg	4.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	4
Starting Capacitor Microf	8
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.