



Pacchetti Motore Sincrono PM e Azionamento - IES2

MOTORE PM CON AZIONAMENTO INTEGRATO - IES2

- Massima integrazione per performance sempre migliori
- Motore IE5 + VFD IE2
- L'affidabilità di un motore AC e le prestazioni di un Brushless

HP Integral
Smart Flow Plus
solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPI 90 1800 46_Flow 2.2 kW - 1800 rpm | Drive three-phase - 200-240V

PERFORMANCE DATA

| | |
|---------------------------------|---------------------|
| Package Type | HPI 90 1800 46_Flow |
| Rated Speed rpm | 1800 |
| Rated Power kW | 2.2 |
| Rated Power HP | 3 |
| Rated Torque Nm | 11.7 |
| Peak Torque Nm | 17.5 |
| Rated Current Arms | 4.6 |
| Peak Current Arms | 7.0 |
| Rated input current 380Vac Arms | 4.9 |
| Rated input current 480Vac Arms | 3.9 |
| Torque Constant Nm/A | 2.5 |
| HPI Weight kg | 15.5 |
| Motor Efficiency IE code | IE5 |

| | |
|---------------------------------|------|
| Drive Type | Flow |
| Drive Efficiency IE code | IE2 |
| HPI Efficiency IE code | IES2 |
| HPI Efficiency ? % | 89.6 |

Mechanical Data

| | |
|-----------------------------|-------------------------------|
| Design | ALUMINIUM |
| Degree of protection | IP 55 |
| Bearings DE | 6206 2Z |
| Bearings NDE | 6304 2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |

Electrical Data

| | |
|------------------------------|----------------|
| Supply Voltage | 400V - 50Hz |
| Duty type | S1 |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -15°C / +40 °C |
| Altitude | 1001 m.a.s.l. |

Drive Data

| | |
|------------------------|--|
| Drive Type | Flow |
| Supply Voltage | three-phase |
| Drive Voltage | 200-240V |
| Safety Function | STO/PLC |
| Drive Torque | variable |
| Fieldbus | BACnet MS/TP; Modbus RTU |
| Inputs | 3 Digital (+3 optional); 2 Analog / Digital selectable |
| Outputs | 2 Analog / Digital; 2 Relays (+3 optional) |

