

Pacchetti Motore Sincrono PM e Azionamento - IES2



MOTORE PM E AZIONAMENTO COMBINATO - IES2

- Soluzione Plug & Play
- Totale controllo della velocità
- Protezione IP20 o IP66 / NEMA 4X outdoor
- Tre configurazioni del pacchetto

HP Combi
Smart IP20 Flow Plus
solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPC 132 3600_Smart_IP20 30 kW - 3600 rpm | Drive three-phase - 500-600V

PERFORMANCE DATA

Package Type	HPC 132 3600_Smart_IP20
Rated Speed rpm	3600
Rated Power kW	30
Rated Power HP	40
Rated Torque Nm	79.6
Peak Torque Nm	199
Voltage Constant Vs	0.73
Torque Constant Nm/A	1.26
B.E.M.F. @ rated speed Vrs	272
Rated Current Arms	62.9
Motor Efficiency IE code	IE5
Motor Efficiency η %	94.9
Motor Weight Kg	85

Drive Type	Smart
Drive Size	5
Drive Efficiency IE code	IE2
HPC Efficiency IE code	IES2
HPC Efficiency ? %	93.4

Electrical Data

Motor Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.

Drive Data

Drive Type	Smart
Drive Size	5
Supply Voltage	three-phase
Drive Voltage	500-600V
Safety Function	-
Drive Torque	constant/variable
Fieldbus	CANopen; Modbus RTU
Inputs	2 Digital; 2 Analog / Digital selectable
Outputs	1 Analog/Digital; 1 Relay
Degree of Protection	IP 20