



Motori Sincroni PM - IE6/IE5

MOTORI ULTRA PREMIUM EFFICIENCY - IE5

- Rendimento IE5 Ultra Premium Efficiency
- L'affidabilità di un motore AC con le prestazioni di un Brushless
- Gamma completa e sempre disponibile a stock



TECHNICAL DATA

Motor Type

IE5 HPS 56 3000 12 0.55 kW - 3000 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE5 HPS 56 3000 12
Rated Speed rpm	3000
Rated Power kW	0.55
Rated Power HP	0.75
Rated Torque Nm	1.8
Peak torque Nm	5.3
Voltage constant Vs	0.87
Torque constant Nm/A	1.5
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	1.2
Efficiency IE code	IE5
Efficiency η %	82.7
Weight Kg	3.2

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6202 2Z
Bearings NDE	6201 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.