



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI HIGH EFFICIENCY - IE2

- Personalizzazione a tutti i livelli



TECHNICAL DATA

Motor Type

AMMHE 71Z AA4 - 0.25 kW - 4 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMMHE 71Z AA
Poles	4
kW	0.25
HP	0.33
rpm	1395
Mn Nm	1.7
η 100%	68.50
cos Phi	0.97
I_N 230V	1.6
I_A/I_N	3.0
M_A/M_N	0.5
M_K/M_N	1.4
J 10^{-3} kgm ²	1.12
kg	8.9

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	10
Starting Capacitor Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.