



**Motori Asincroni Trifase - IE4/IE3/IE2/IE1**

**MOTORI HIGH EFFICIENCY - IE2**

- Personalizzazione a tutti i livelli



## TECHNICAL DATA

**Motor Type**

AMMHE 80Z BA4 - 0.55 kW - 4 poles - 230V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMMHE 80Z BA
<b>Poles</b>	4
<b>kW</b>	0.55
<b>HP</b>	0.75
<b>rpm</b>	1450
<b>Mn Nm</b>	3.6
$\eta$ 100%	77.10
<b>cos Phi</b>	0.91
<b>I<sub>N</sub> 230V</b>	3.4
<b>I<sub>A</sub>/I<sub>N</sub></b>	4.7
<b>M<sub>A</sub>/M<sub>N</sub></b>	0.4
<b>M<sub>K</sub>/M<sub>N</sub></b>	1.9
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	2.80
<b>kg</b>	13.1

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6204/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	48

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	14
<b>Starting Capacitor Microf</b>	-
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.