



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 56Z BA2 - 0.12 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 56Z BA
Poles	2
kW	0.12
HP	0.16
rpm	2800
Mn Nm	0.4
η 50%	51.0
η 75%	56.0
η 100%	62.0
cos Phi	0.68
I_N 400V	0.40
I_N 380-420V	0.45
I_A/I_N	3.5
M_A/M_N	3.4

M_S/M_N	3.4
M_K/M_N	3.5
J 10⁻³ kgm²	0.1
kg	3.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6201/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.