



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI STANDARD EFFICIENCY - IE1

- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AM 63Z AA2 - 0.18 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 63Z AA
Poles	2
kW	0.18
HP	0.25
rpm	2790
Mn Nm	0.6
η 50%	54.0
η 75%	58.0
η 100%	63.0
cos Phi	0.73
I _N 400V	0.60
I _N 380-420V	0.65
I _A /I _N	3.7
M _A /M _N	3.0

M_S/M_N	3.0
M_K/M_N	3.1
$J \cdot 10^{-3} \text{ kgm}^2$	0.14
kg	3.6

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.