



**Motori Asincroni Trifase - IE4/IE3/IE2/IE1**

**MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS**

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



## TECHNICAL DATA

**Motor Type** AMQE 280M G2 - 90 kW - 2 poles - 400V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMQE 280M G
<b>Poles</b>	2
<b>kW</b>	90
<b>HP</b>	125
<b>rpm</b>	2982
<b>Mn Nm</b>	288.2
$\eta$ 50%	93.9
$\eta$ 75%	95.8
$\eta$ 100%	95.8
<b>cos Phi</b>	0.90
<b>I<sub>N</sub> 400V</b>	151.0
<b>I<sub>N</sub> 460V</b>	-
<b>I<sub>N</sub> 575V</b>	-
<b>I<sub>A</sub>/I<sub>N</sub></b>	7.1

$M_A/M_N$	1.8
$M_S/M_N$	1.7
$M_K/M_N$	2.3
$J \cdot 10^{-3} \text{ kgm}^2$	675
kg	630

## Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6314 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	1.000 hours
Regreasing device vertical	1.000 hours
Grease Quantity	35 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	71

## Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.