



Motori Asincroni Trifase - IE4/IE3/IE2/IE1

MOTORI SUPER PREMIUM EFFICIENCY - IE4/CURUS

- Ampia gamma 0.75 - 200kW
- Affidabilità assoluta: solido, prestante, duraturo
- Infinite possibilità di personalizzazione per ogni esigenza applicativa



TECHNICAL DATA

Motor Type

AMQE 160M BA44 - 11 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMQE 160M BA4
Poles	4
kW	11
HP	15
rpm	1482
Mn Nm	71.3
η 50%	91.7
η 75%	93.0
η 100%	93.3
cos Phi	0.80
I _N 400V	21.4
I _N 460V	-
I _N 575V	-
I _A /I _N	9.1

M_A/M_N	2.5
M_S/M_N	2.0
M_K/M_N	3.2
$J \cdot 10^{-3} \text{ kgm}^2$	120.7
kg	110.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.